Estuarine Detection of PIT-Tagged Juvenile Salmonids Using Pair-Trawls, 2007

Richard Ledgerwood¹, Robert Magie², April Cameron²

¹National Marine Fisheries Service, Point Adams Biological Field Station

²Pacific States Marine Fisheries Commission




Objectives 2007

- Frovide data to complete reach survival estimates for yearling salmonids for the entire.
 Columbia River hybropower system.
- Sample in the fall, targeting Snake River Fall Chinook salmon (cancelled tagging).
- Continue development of a magnitude larger Pit-tag antenna, the "Matrix" used to increase detection efficiency via faster trawling speed.



Columbia Basin PIT tags


Columbia Basin PIT tag Releases and Detections at Bonneville Dam and Jones Beach (Rkm 75)





Daily Sample Effort at Rkm 75







Detections By Species/Run and History

| Large Trawl Jones Beach Detections 2007 | | | | |
|---|--------|-------|------|--------|
| Species/run | Hat. | Wild | Unk. | Total |
| Spring/summer Chinook salmon | 12,358 | 1,854 | 107 | 14,319 |
| Fall Chinook salmon | 471 | 31 | 78 | 580 |
| Coho salmon | 270 | 0 | 20 | 290 |
| Steelhead | 2,165 | 1,321 | 6 | 3,492 |
| Sockeye | 214 | 32 | 0 | 246 |
| Searun Cutthroat | 0 | 0 | 0 | 0 |
| Unknown | 0 | 0 | 259 | 259 |
| Grand total | 15,478 | 3,238 | 470 | 19,186 |

Source of Juveniles Detected in the Estuary 2007 n=19,186

Snake River 80%

n = 15,400

Upper Columbia River 11% n = 2065

Mid Columbia River n = 854 Lower Columbia River n = 598 Other n = 258

History of Juvenile Salmonids
Detected in the Estuary
n=19,186

Detected at

Bonneville Dam

71%




Detected at Bonneville 13%



Estuary Detections of Yearling Chinook Salmon and Steelhead Previously Detected at Bonneville Dam, 2007


Yearling Chinook Salmon (mean = 3.4%)

Steelhead (mean = 3.5%)





Mean Hourly Detections, 2007




Time of Day



Flow (m³/s)

Travel Speed Bonneville Dam to the Estuary for Yearling Chinook Salmon


- ▲ In-river (Detected at Bonneville Dam), mean 90
- Barged (Released Below Bonneville Dam), mean 71





Estuary Detection Rates of Yearling Chinook Salmon











Survival (SE) from McNary to Bonneville Dam

Yearling Chinook salmon



- Snake River stock
- Upper-Columbia stock

Steelhead



Seasonal weighted Averages from weekly estimates



Large Pair-Trawl Antenna Used in 2007

Fish passage tunnel

Front and rear coils for dual detections

Detection percentage of test tags passed through the center of each coil = 74 to 85%*

* Properly tuned system reads over 95% of these same tags when passed within 8" of antenna wall.




Matrix Antennas Used in 2007

Detection percentage of test tags passed through the center of each coil

Rear










Matrix vs. Large Trawl Detections



- Matrix System*
- Large Trawl System

Antenna On-Time

= 40 hr 13 min

<u>Total Detections</u>

Matrix = 234

Large Trawl = 829



Antenna On-Time

Matrix = 16hrs 23min

Large Trawl = 16hrs 5min

Total Detections

Matrix = 67

Large Trawl = 12



Summary--survival

- Survival for in-river migrants from Lower Granite Dam to Bonneville Dam in 2007 was similar to 2006, despite much lower flow volume in 2007; 59% and 39% yearling Chinook salmon and steelhead, respectively.
- Survival from McNary Dam to Bonneville Dam in 2007 for upper Columbia River yearling Chinook salmon (71%) was higher than in recent years when estimates were possible but lower than for Snake River source fish (76%).
- Survival from McNary Dam to Bonneville Dam in 2007 for upper Columbia River steelhead (39%) was considerably lower than for Snake River steelhead (56%) and lower than in recent years when estimates were possible for these stocks (range 41% to 70%).

Summary—sample efficiency

- Detection rate in 2007 was higher than in any previous year (3.4% of fish previously detected at Bonneville Dam).
- The enlarged Matrix antenna system has the potential to greatly increase sample efficiency through reduced drag and increased tow speed (nearly double). We will test a 6-coil Matrix (3 front and 3 rear coils) and possibly switch to that system entirely in 2008.

